

**TH-2500 – DUAL ARM COMBINATION TOPPER HEDGER**  
SPECIFICATION SHEET

**SPECIFICATIONS:**

- CUTTING ARM DIAMETER ( EACH ARM).....13' (396 CM)**
- TOTAL CUTTING PASS (TWO ARMS COMBINED).....24' (730 CM)**
- MAXIMUM HEDGING POSITION HEIGHT.....44' (1341 CM)**
- MAXIMUM FLAT TOPPING HEIGHT.....19' (580 CM)**
- MAXIMUM REACH FROM CENTER FLAT TOPPING .....25'6" (777 CM)**
- CUTTING ANGLE BETWEEN ARMS (GABLE TOP).....0<sup>0</sup> - 30<sup>0</sup>**
- TRANSPORT HEIGHT.....10'8" (325 CM)**
- MACHINE WEIGHT.....28,000 LBS (12700 KG)**
- SAW BLADES.....4 - 32" DIAMETER, PROPRIETARY SAW BLADES**

**SELF PROPELLED POWER UNIT:**

**Includes the following components:**

- ITL** heavy duty front and rear axles
- JOHN DEERE** 6068T Tier 3, 155 HP (at 2500 RPM), turbo charged diesel engine
- JOHN DEERE / FUNK** pump drive
- JOHN DEERE / FUNK** 2-speed transmission
  - Operating mode: 0 – 5 MPH
  - Transport mode: 0 – 12 MPH
- EATON** hydrostatic drive system
- Heavy Duty front and rear rims and tires
  - Rear tires 16.9 x 34 – 18 ply forestry tires
  - Front tires 14.9 x 24 – 18 ply forestry tires

**HYDRAULIC SYSTEM:**

- Saw blade rotation circuit – **VOAC** piston pump and motor
- Arms rotation circuit – **EATON** variable displacement, piston pump with 2000 series **CHAR LYNN** motor.
- Control circuit – Gear type pump operating:
  - Tower lift cylinder
  - Horizontal to vertical cylinder
  - Arms swing cylinder
  - Arms transport cylinder
  - Engine hood lift cylinder
  - Front axle stabilizer cylinder
- Hydrostatic drive circuit – **EATON** pump and motor.
- Cooling package fan circuit – gear type pump.

**SAW BLADES SYSTEM:**

- 4 - 32" heavy duty, proprietary saw blades.
- Double belt drive on each saw blade for durability.
- Double row, sealed, roller bearings for the saw bearing housings for long lasting, trouble free operation.

**OPERATOR CAB:**

The large, heavy duty, flat-deck operator's cab is mounted as a separate unit on rubber mounts to reduce noise, vibration and heat. Pressure gauges mounted on the control panel allow the operator to continually monitor the machine load. The front windows of the cab are made of tempered glass providing unobstructed vision and safety. The side windows are covered with laser cut metal screens for ventilation (air conditioned cabs include tempered glass on the side windows).

**COOLING SYSTEM :**

A self-cleaning cooling system mounted at the rear of the machine contains three radiators for the following:

- Engine coolant
- Hydraulic oil
- Air conditioning condenser

A maintenance free, automatic vacuum system removes and discharges debris before it gets to the radiators to ensure constant operation under normal working temperature.

**SAFETY:**

In the design, components selection, and manufacturing, as well as in the servicing and operating instructions, much thought has been given to provide a machine with high productivity, low maintenance, long life, and above all operator safety.

**LITERATURE:**

Each unit is supplied with full documentation for all systems. This includes a "General Safety & Operations Manual" and "Specifications and Spare Parts Manual".

**FINISH:**

- Machine parts are sand blasted, primed and painted.
- Machine bolts are zinc plated, grade 5.
- Saw blade propelling and rotation parts (pulleys, shafts, washers, etc.) are zinc plated.
- The machine is assembled and each system is fully tested. Final adjustments are made to ensure the machine is ready for use

**Note:** Some parts are disassembled for shipping.

**PRICE:**

Please inquire for pricing.

**OPTIONS:**

- Air conditioned cab
- Air conditioned and heated cab
- Forward and rear view camera system

**SALE CONDITIONS**

- PRICES** F.O.B., TOL Incorporated
- DELIVERY** According to availability
- TERMS** 20% deposit required to confirm an order.  
Balance due on delivery.

**PACKING:**

One machine in 40' Container.

**NOTES:**

As our policy is of continuous improvement, we reserve the right to change specifications without prior notice.